





pical Note for a Painted Finish

- NOTES:

 1. FIELD VERIFICATION OF ALL DIMENSIONS IS REQUIRED BEFORE CONSTRUCTION OF SHELL COMPONENTS.
- ALL RIGGING AND RIGGING HARDWARE IS TO BE SUPPLIED AND INSTALLED BY GENERAL CONTRACTOR OR OWNER (NOT IN WENGER CONTRACT).
- ALL RIGGING, RIGGING HARDWARE AND LIGHTING IS TO BE SUPPLIED AND INSTALLED BY GENERAL CONTRACTOR OR OWNER (NOT IN WENGER CONTRACT).
- 5. ALL FINISHES OF THE ACOUSTICAL ENCLOSURE TO BE LISTED BELOW.

 (A) THE FACE SIDE OF PANELS IS TO BE PAINTED A COLOR AS SPECIFIED BY OTHERS.
- (A) THE FACE SIDE OF PANELS IS TO BE PAINTED A COLOR AS SPECIFIED BY OTHERS.
 (B) THE WOOD DACK SIDE OF PANELS TO BE PAINTED BLACK.
 (C) THE TOWER TRIM STRIP TO BE PAINTED A COLOR AS SPECIFIED BY OTHERS. WE PREFER YOU CHOOSE ANY SHEWIN WILLIAMS COLOR FROM THEIR INTERIOR PALETTE.
 (D) CAP SCREWS, LOCK NUTS, AND ALL OTHER PURCHASED HARDWARE WILL HAVE STANDARD MANUFACTURESES FINISH.
- ALL LIGHTS ARE TO BE A SOURCE FOUR PAR "MON" LIGHT FIXTURE BY (ELECTRONIC THEATER CONTROLS). EACH INDIVIDUAL LIGHT FIXTURE WILL BE WIRED TO A TERMINAL BLOCK LOCATED. EITHER END OF EACH ROW. THE MULTI-CABLE, DROP BOX OR RELATED HARDWARE REQUIRED TO

pical Note for a Stained Finish

- NUTES:

 1. FIELD VERIFICATION OF ALL DIMENSIONS IS REQUIRED BEFORE CONSTRUCTION OF SHELL
 COMPONENTS.
- 2. ACOUSTICAL PANES, ARE CONSTRUCTED OF \$ 1/2" THICK FIRER HOMERCOMS WITH 14" WHITE OAK, RED OAK, MAREL, BEICH, DESERVI VEERS HOM FAVYOOD ON THE FACE SIZE AREO 31.5" MINISTRUCTURE. PRINCE SIRRAFES ON MERY 11/2" DO THE METERIAL TO SEARCHES, DIRECT DOWN LIGHTING ON THE WALL TO THE WITHOUT CONSIDERATED. THE FORMES SHAFFLES THE FORMES AND THE TOWN SHAFFLES AND THE FORMES AND THE TOWN SHAFFLES THE TOWN SHAF
- THIS GRADE, WOOD GRAIN PATTERNS AND COLOR OF WOOD WILL VARY FROM PANEL TO PANEL.
- ALL RIGGING AND RIGGING HARDWARE IS TO BE SUPPLIED AND INSTALLED BY GENERAL CONTRACTOR OR OWNER (NOT IN WENGER CONTRACT).
- ALL RIGGING, RIGGING HARDWARE AND LIGHTING IS TO BE SUPPLIED AND INSTALLED BY GENERAL CONTRACTOR OR OWNER (NOT IN WENGER CONTRACT).
- ALL PANEL FINISHES OF THE ACOUSTICAL ENCLOSURE TO BE LISTED BELOW.

 AN THE EAST CITIE OF DANIEL TO BE CTAINED A COLOR OF CRESTEEN BY ATHERE WHENCE

 AND THE EAST CITIES OF DANIEL TO BE CTAINED A COLOR OF CRESTEEN BY ATHERE WHENCE

 THE PANEL FINISHES OF THE ACOUSTICAL ENCLOSURE TO BE LISTED BELOW.

 AND THE EAST CITIES OF DANIEL TO BE CTAINED A COLOR OF CRESTEEN BY ATHERE WHENCE

 THE PANEL FINISHES OF THE ACOUSTICAL ENCLOSURE TO BE LISTED BELOW.

 AND THE EAST CITIES OF DANIEL TO BE CTAINED A COLOR OF CRESTEEN BY ATHERE WHENCE

 THE PANEL FINISHES OF THE ACOUSTICAL ENCLOSURE TO BE LISTED BELOW.

 AND THE EAST CITIES OF DANIEL TO BE CTAINED A COLOR OF CRESTEEN BY ATHERE WHENCE

 THE PANEL FINISHES OF THE ACOUSTICAL ENCLOSURE TO BE LISTED BELOW.
- (A) THE PINE SIZE OF PARIES TO BE STATINED A COLOR AS SPECIFIED BY OTHERS, WENGERS STANDARD IS A WIPING STAIN BY SERVIN WILLIAMS. THE FINAL FINISH CONSISTS (TWO COATS SHERWIN WILLIAMS CAB ACRYLIC LACQUER.

 (B) THE WOOD BACK SIDE OF PARIES TO BE PAINTED BLACK.
 (C) THE TOWER TRIM STOP TO BE PAINTED A COLOR AS SPECIFIED BY OTHERS. WE PREFER
- (D) CAP SCREWS, LOCK NUTS, AND ALL OTHER PURCHASED HARDWARE WILL HAVE STAN MANUFACTURER'S FINISH.

 7. ALL LIGHTS ARE TO BE A SOURCE FOUR PAR "MOM" LIGHT FIXTURE BY (ELECTRONIC THEATER CONTROLS). EACH INDIVIDUAL LIGHT FIXTURE WILL BE WIRED TO A TERMINAL BLOCK LOCATE

Typical Note for a Wilsonart Laminate Finis

- 1. FIELD VERIFICATION OF ALL DIMENSIONS IS REQUIRED BEFORE CONSTRUCTION OF SHELL COMPONENTS.
- 2. ACOUSTICAL PANELS ARE CONSTRUCTED OF 1 1/2" THICK FIBER HONEYCOMB WITH 3/16" MASONI MAGGOADO ON 507H SIZES (TOTAL IN-DOSSESS FT 3/19"). THE ALLOWENEY IS TWO ADDICATION LOGISTICS OF THE ALLOWENEY IS TWO ADDICATION LOGISTICS OF THE ALTOWERS WILL HIGHLIGHT WASHINGS RETWEST THE PROS. SUPERAL STATES THE SET OF THE TOWN OF THE TOWNS SHOULD BE AVOIDED WHENEVER POSSIBLE SET WOOD STATES ALLOWED, SET AND STATES ALLOWED, SET ALLOWED, SET ALLOWED, SET ALLOWED, SET AND STATES ALLOWED, SET ALLOWED, SE
- ALL RIGGING AND RIGGING HARDWARE IS TO BE SUPPLIED AND INSTALLED BY GENER CONTRACTOR OR OWNER (NOT IN WENGER CONTRACT).
- CONTRACTOR OR OWNER (NOT IN WENGER CONTRACT).

 OR
- ALL RIGGING, RIGGING HARDWARE AND LIGHTING IS TO BE SUPPLIED AND INSTALLED BY G CONTRACTOR OR OWNER (NOT IN WENGER CONTRACT).
- WEIGHT OF CELLINGS IS CALCULATED AND DOES NOT INCLUDE RIGGING OF RIGGING HARDWAY
 ALL PAINEL PAINTED FINISHES OF THE ACOUSTICAL ENCLOSURE TO BE LISTED BELOW. LAMINA'
- ALL PANSE, PAINTED FINISHES OF THE ACOUSTICAL ENCLOSURE TO BE LISTED BELOW. LAWINAT SUPPLIED FOR ACOUSTICAL ENCLOSINE TO BE CLASS "C. SC.," CR. ADD. THE FIRST TO BE (A) THE FACE SIDE OF PANSELS IS WILSOWART LAWINATE, CLASSIC GRADE, TYPE 117. FINISH TO BE #60, MATTE, TEXTURED-GRAIN PATTERS DO NOT MATCH FROM PANEL TO PANSEL COLOR A:
- (B) THE WOOD BACK SIDE OF PANIES TO BE PAINTED BLICK.
 (C) THE TOWER TRIM STRIP TO BE PAINTED A COLOR AS SPECIFIED BY OTHERS. WE PREF
 YOU CHOOSE ANY SHERWIN WILLIAMS COLOR FROM THEIR INTERIOR PALETTE.
 (D) CAP SCREWS, LOCK NUTS, AND ALL OTHER PURCHASED HARDWARE WILL HAVE STAND
 MANUFACTHERSE FRINGH
- 6. ALL LIGHTS ARE TO BE A SOURCE FOUR PAR "MON" LIGHT FIXTURE BY (ELECTRONIC THEATER CONTROLS), EACH INDIVIDUAL LIGHT FIXTURE WILL BE WIRED TO A TERMINAL BLOCK LOCATED ETHER RING OF EACH ROW. THE MILIT-CABLE, DROP BOX OR RELATED HARDWARE REQUIRED TO SUPPLY THE PROMPS TO THE TERMINAL BY CAY IS TO BE SUPPLYED HEAD AND MISSIED BY AND THE CONTROL OF THE PROMPS TO THE TERMINAL BY CAY IS TO BE SUPPLYED HEAD AND MISSIED BY OTHER DESCRIPTION.



NOTES

- 1. ESTIMATED CEILING WEIGHTS ARE 4 POUNDS PER SQUARE FOOT
- 2. ADD 25 POUNDS FOR EACH INCANDESCENT LIGHT FIXTURE ASSEMBLY
- 3. ADD 35 POUNDS FOR EACH LED LIGHT FIXTURE ASSEMBLY
- 4. RECOMMEND A TRUSS BATTEN FOR 9', 10', 11' AND 12' CEILING ROWS
- 5. RECOMMEND A TRUSS BATTEN FOR ALL FLOWN REAR WALLS

DIVA/MAESTRO SYMBOLS

507-455-4100