GEARBOSS 2 CART NOTES:

- 1. BEFORE THE PRODUCTION OF WENGER COMPONENTS BEGINS, THE ROOM DIMENSIONS AND EQUIPMENT LAYOUT SHOWN ON THIS DRAWING, INCLUDING ANY CEILING OR WALL OBSTRUCTIONS THAT MAY INTERFERE WITH THE MOVEMENT OR OPERATION OF THE GEARBOSS SYSTEM, MUST BE CONFIRMED BY THE GENERAL CONTRACTOR AND/OR FACILITY OWNER.
- 2. THE INSIDE EDGE OF THE BACK FLOOR TRACK IS MOUNTED A MINIMUM OF 4 1/2" FROM A REAR WALL TO ALLOW 1" OF CLEARANCE BEHIND THE CARTS. THE INSIDE EDGE OF THE FRONT FLOOR TRACK SHOULD BE MOUNTED 66 1/4" FROM THE INSIDE EDGE OF THE BACK TRACK.
- 3. FLOOR MUST BE FLAT (1/8" IN 4') AND SMOOTH WHERE THE CART WHEELS NORMALLY PASS. OPTIMUM FLOOR IS CONCRETE.
- 4. WHEN INCLUDED IN THE CONTRACT, INSTALLATION INCLUDES THE ASSEMBLY OF CARTS AND ACCESSORIES AND THE INSTALLATION OF THE FLOOR TRACK.



